



Technical Adhesive Tapes

Individual product
selection

Coroplast
— tape

Coroplast 832 MPX TT

TapeTubes for highly flexible wire harness protection

Characteristics

- ✓ Developed specifically to eliminate the contact between adhesive and wire bundle allowing maximum harness flexibility
- ✓ Especially suitable for time-saving processes on long harness sections without junctions
- ✓ Very good resistance to cold and heat
- ✓ Compressible, therefore advantaged in assembly and logistics compared to other covering systems
- ✓ Solvent-free adhesive
- ✓ Halogen-free
- ✓ PVC-compatible
- ✓ Very good chemical resistance
- ✓ No 'inner' abrasion
- ✓ Multilayer PA cloth
- ✓ Outstanding abrasion resistance
- ✓ Dense textile structure of PA carrier
- ✓ Tear-proof
- ✓ Suitable for cable protection in accordance with ADR 2017



| | 832 MPX TT | 837 X TT |
|-------------------------|------------|-----------|
| CARRIER | PA cloth | PET cloth |
| ADHESIVE | Acrylic | Acrylic |
| THICKNESS IN mm | 0,7 | 0,46 |
| ABRASION CLASSES | G | E |
| SOUND DAMPENING CLASSES | B | B |
| HEAT RESISTANCE | 125 | 150 |

Your contact

Do you have further questions about our adhesive tape offer? Then you are welcome to contact us at any time.

Sina Kammann
Business Field Manager Wire Harness
Industry

T +49 202 2681 442
sina.kammann@coroplast-tape.com

Coroplast 837 X TT

TapeTubes for highly flexible wire harness protection

Characteristics

- ✓ Developed specifically to eliminate the contact between adhesive and wire bundle allowing maximum harness flexibility
- ✓ Especially suitable for time-saving processes on long harness sections without junctions
- ✓ Very good resistance to cold and heat
- ✓ Compressible, therefore advantaged in assembly and logistics compared to other covering systems
- ✓ Solvent-free adhesive
- ✓ Halogen-free
- ✓ PVC-compatible
- ✓ Very good chemical resistance
- ✓ No 'inner' abrasion
- ✓ Highly temperature resistant
- ✓ High abrasion resistance
- ✓ Tear-proof



| | 832 MPX TT | 837 X TT |
|-------------------------|------------|-----------|
| CARRIER | PA cloth | PET cloth |
| ADHESIVE | Acrylic | Acrylic |
| THICKNESS IN mm | 0,7 | 0,46 |
| ABRASION CLASSES | G | E |
| SOUND DAMPENING CLASSES | B | B |
| HEAT RESISTANCE | 125 | 150 |

Your contact

Do you have further questions about our adhesive tape offer? Then you are welcome to contact us at any time.

Sina Kammann
Business Field Manager Wire Harness
Industry

T +49 202 2681 442
sina.kammann@coroplast-tape.com



**Coroplast Fritz Müller
GmbH & Co. KG**

Wittener Straße 271
42279 Wuppertal
Germany

T +49 202 2681 139
info-de@coroplast-tape.com
www.coroplast-tape.com

**Coroplast Tape Technology
(Kunshan) Co., Ltd.**

Building N #299 Yuyang Rd,
Plainvim Industrial Park
215300 Kunshan,
Jiangsu Province, China

T +86 512 366 518 80
info-cn@coroplast-tape.com
www.coroplast-tape.cn

Coroplast Tape Corporation

1230 Galleria Boulevard
Rock Hill, South Carolina,
29730, USA

T +1 803 2078 334
info-us@coroplast-tape.com
www.coroplast-tape.com

Our products are the result of thorough research. They are state of the art. To assist in the usefulness of a product, we give data and technical information to the best of our knowledge, but without any warranty or guarantee. This information shall be considered as average values and are not appropriate for a customer or supplier specification. The data and technical information contained herein do

not constitute an agreement on the characteristics of the product. We expressly reserve the right to make technical modifications to all our products.

Note: Before use, the suitability of the product for the specific application must be examined by the user.